



Nano pulsar round


Nano pulsar square



Technical Information

Power	3,5W	3,5W
Installation	Recessed	Recessed
Color Temperature	2.700K / 3.000K / 4.000K	2.700K / 3.000K / 4.000K
Lumens	170 lm / 180 lm / 200 lm	170 lm / 180 lm / 200 lm
Material	Aluminium	Aluminium
Finishes	White / Black	White / Black

Code	<input type="checkbox"/> 2.700K 4297	<input type="checkbox"/> 2.700K 4451
	<input type="checkbox"/> 3.000K 4298	<input type="checkbox"/> 3.000K 4452
	<input type="checkbox"/> 4.000K 4299	<input type="checkbox"/> 4.000K 4453
	<input checked="" type="checkbox"/> 2.700K 4300	<input checked="" type="checkbox"/> 2.700K 4454
	<input checked="" type="checkbox"/> 3.000K 4301	<input checked="" type="checkbox"/> 3.000K 4455
	<input checked="" type="checkbox"/> 4.000K 4302	<input checked="" type="checkbox"/> 4.000K 4456
	<input checked="" type="checkbox"/> Custom RAL	<input checked="" type="checkbox"/> Custom RAL



ⓘ Consult delivery terms and conditions.

3 YEARS WARRANTY | 30.000 HOURS | IP 65 | 220/240 VAC | UGR <16 | PF >0,5 | CRI ≥80 | 30° | 50/60 Hz | | +40°C / -20°C | 1/50