


Time



Control accessories pages 282-289.



Technical Information

Power	31W / 46W / 69W
Lumens	3.472 lm - 9.384 lm
Installation	Surface / Pendant
Material	Aluminium
PCB	Rigid

Code	Diffuser (Angle)	Size	CCT (lm/W) - Power/m	Driver	Colour
Code 8	UGR (81°) 3	1.130mm 3	2.700K (112 lm/W) - 27W/m 2	On / Off 1	<input type="checkbox"/> White (9003) 1
	Opal (112°) 5	1.690mm 5	3.000K (128 lm/W) - 27W/m 3	Dali 2	<input type="checkbox"/> Black (9005) 2
		2.530mm 7	4.000K (136 lm/W) - 27W/m 4	Push 3	<input type="checkbox"/> Gray (9006) 3
			5.000K (136 lm/W) - 27W/m 5	Casambi 5	<input type="checkbox"/> Custom RAL C
					<input type="checkbox"/> Electrolytic Plating

Code: **8**

*Create your code according to your preferences.

Consult delivery terms and conditions.

Accessories

End caps <input type="checkbox"/> 40741 <input type="checkbox"/> 40742 <input type="checkbox"/> 40743	Joint 180° <input type="checkbox"/> 40770	Joint 90° <input type="checkbox"/> 40990	Wall bracket <input type="checkbox"/> 40851 <input type="checkbox"/> 40852 <input type="checkbox"/> 40853	Trimless <input type="checkbox"/> 40339	Base 3x0,75 (2,5m) Ø60x28mm <input type="checkbox"/> 40881 <input type="checkbox"/> 40882 <input type="checkbox"/> 40883	Base 5x0,5 (2,5m) Ø60x28mm <input type="checkbox"/> 40991 <input type="checkbox"/> 40992 <input type="checkbox"/> 40993	Ceiling suspension <input type="checkbox"/> 40780	Suspension kit <input type="checkbox"/> 40790 (2m)



Accessories pages 158-159.

