


Time E



43mm x L



\*Spring clips included. Control accessories pages 282-289.

Technical Information

Power	31W / 46W / 69W
Lumens	3.472 lm - 9.384 lm
Installation	Recessed
Material	Aluminium
PCB	Rigid

Code	Diffuser (Angle)	Size	CCT (lm/W) - Power/m	Driver	Colour
Code <b>9</b>	UGR (81°) <b>3</b>	1.130mm <b>3</b>	<b>2.700K</b> (112 lm/W) - 27W/m <b>2</b>	On / Off <b>1</b>	<input type="checkbox"/> White (9003) <b>1</b>
	Opal (112°) <b>5</b>	1.690mm <b>5</b>	<b>3.000K</b> (128 lm/W) - 27W/m <b>3</b>	Dali <b>2</b>	<input checked="" type="checkbox"/> Black (9005) <b>2</b>
		2.530mm <b>7</b>	<b>4.000K</b> (136 lm/W) - 27W/m <b>4</b>	Push <b>3</b>	<input type="checkbox"/> Gray (9006) <b>3</b>
			<b>5.000K</b> (136 lm/W) - 27W/m <b>5</b>	Casambi <b>5</b>	<input checked="" type="checkbox"/> Custom RAL <b>C</b>
					<input checked="" type="checkbox"/> Electrolytic Plating

Code: **9**

\*Create your code according to your preferences.

Consult delivery terms and conditions.


Accessories



End caps  
 40751  
 40752  
 40753

Joint 180°  
 40770

Joint 90°  
 40990



Accessories pages 158-159.

