


Urban



Control accessories pages 282-289.

Technical Information

Power	46W / 57W / 69W / 80W / 103W
Lumens	5.152 lm - 14.008 lm
Installation	Surface / Pendant
Material	Aluminium
PCB	Rigid

Code	Diffuser (Angle)	Size	CCT (lm/W) - Power/m	Driver	Colour
Code 6	UGR (78°) 4	1.130mm 3	2.700K (112 lm/W) - 40W/m 2	On / Off 1	<input type="checkbox"/> White (9003) 1
	Opal (112°) 5	1.410mm 4	3.000K (128 lm/W) - 40W/m 3	Dali 2	<input type="checkbox"/> Black (9005) 2
		1.690mm 5	4.000K (136 lm/W) - 40W/m 4	Push 3	<input type="checkbox"/> Gray (9006) 3
		1.970mm 6	5.000K (136 lm/W) - 40W/m 5	Casambi 5 ⓘ	<input type="checkbox"/> Matt Gold 4
		2.530mm 7	2.700-5.500K (105 lm/W) - 40W/m 9	Tuya 7 ⓘ	<input type="checkbox"/> Corten 6
					<input type="checkbox"/> Copper 7
					<input type="checkbox"/> Custom RAL C
					<input type="checkbox"/> Electrolytic Plating ⓘ


Code: **6**

ⓘ Consult delivery terms and conditions.

*Create your code according to your preferences. CCT 2.700-5.500K only works with driver 5 Casambi and 7 Tuya.

Accessories

End caps <input type="checkbox"/> 40721 <input type="checkbox"/> 40722 <input type="checkbox"/> 40723	Joint 180° <input type="checkbox"/> 40220	Joint 90° <input type="checkbox"/> 40550	Wall bracket <input type="checkbox"/> 40851 <input type="checkbox"/> 40852 <input type="checkbox"/> 40853	Trimless <input type="checkbox"/> 40669	Base 3x0,75 (2,5m) Ø60x28mm <input type="checkbox"/> 40881 <input type="checkbox"/> 40882 <input type="checkbox"/> 40883	Base 5x0,5 (2,5m) Ø60x28mm <input type="checkbox"/> 40991 <input type="checkbox"/> 40992 <input type="checkbox"/> 40993	Ceiling suspension <input type="checkbox"/> 40780	Suspension Kit <input type="checkbox"/> 40790 (2m)



Accessories pages 158-159.

