


Urban E



63mm x L



Control accessories pages 282-289.

\*Spring clips included.

Technical Information

Power	46W / 57W / 69W / 80W / 103W
Lumens	5.152 lm - 14.008 lm
Installation	Recessed
Material	Aluminium
PCB	Rigid

Code	Diffuser (Angle)	Size	CCT (lm/W) - Power/m	Driver	Colour
Code <b>3</b>	UGR (78°) <b>4</b>	1.130mm <b>3</b>	<b>2.700K</b> (112 lm/W) - 40W/m <b>2</b>	On / Off <b>1</b>	<input type="checkbox"/> White (9003) <b>1</b>
	Opal (112°) <b>5</b>	1.410mm <b>4</b>	<b>3.000K</b> (128 lm/W) - 40W/m <b>3</b>	Dali <b>2</b>	<input checked="" type="checkbox"/> Black (9005) <b>2</b>
		1.690mm <b>5</b>	<b>4.000K</b> (136 lm/W) - 40W/m <b>4</b>	Push <b>3</b>	<input type="checkbox"/> Gray (9006) <b>3</b>
		1.970mm <b>6</b>	<b>5.000K</b> (136 lm/W) - 40W/m <b>5</b>	Casambi <b>5</b>	<input checked="" type="checkbox"/> Custom RAL <b>C</b>
		2.530mm <b>7</b>	<b>2.700-5.500K</b> (105 lm/W) - 40W/m <b>9</b>	Tuya <b>7</b>	<input checked="" type="checkbox"/> Electrolytic Plating

Code: **3**

ⓘ Consult delivery terms and conditions.

\*Create your code according to your preferences. CCT 2.700-5.500K only works with driver 5 Casambi and 7 Tuya.

Accessories



End caps  
 40731  
 40732  
 40733



Joint 180°  
 40220



Joint 90°  
 40550



Accessories pages 158-159.

5 YEARS WARRANTY | 50.000 HOURS | IP 40 | UGR <19 | 230 VAC | PF >0,9 | CRI ≥95 | | | | 3,37m Max | | | |