


Urban market



Control accessories pages 282-289.

Technical Information

Power	45W / 55,5W / 66W / 76,5W / 97,5W
Lumens	5.040 lm - 13.552 lm
Installation	Surface / Pendant
Material	Aluminium
PCB	Rigid


Code	Diffuser (Angle)	Size	CCT (lm/W) - Power/m	Driver	Colour
Code <b>2</b>	Asymmetric <b>1</b>	1.130mm <b>3</b>	<b>3.000K</b> (112 lm/W) - 40W/m <b>3</b>	On / Off <b>1</b>	<input type="checkbox"/> White (9003) <b>1</b>
	Double asym. <b>2</b>	1.410mm <b>4</b>	<b>4.000K</b> (118 lm/W) - 40W/m <b>4</b>	Dali <b>2</b>	<input checked="" type="checkbox"/> Black (9005) <b>2</b>
	Optical (30°) <b>3</b>	1.690mm <b>5</b>	<b>MEAT R - 3.200K</b> (86 lm/W) - 40W/m <b>R</b>		<input checked="" type="checkbox"/> Custom RAL <b>C</b>
	Optical (60°) <b>6</b>	1.970mm <b>6</b>	<b>HAM - 3.200K</b> (85 lm/W) - 40W/m <b>X</b>		
	Optical (90°) <b>9</b>	2.530mm <b>7</b>	<b>MEAT M - 3.500K</b> (84 lm/W) - 40W/m <b>M</b>		
			<b>FISH - 6.500K</b> (139 lm/W) - 40W/m <b>F</b>		
			<b>FRUIT - 4.200K</b> (123 lm/W) - 40W/m <b>V</b>		
			<b>BREAD - 2.700K</b> (131 lm/W) - 40W/m <b>P</b>		

Code: **2**

Consult delivery terms and conditions.  
\*Create your code according to your preferences.

Accessories

End caps <input type="checkbox"/> 40721 <input checked="" type="checkbox"/> 40722	Joint 180° <input checked="" type="checkbox"/> 40220	Joint 90° <input checked="" type="checkbox"/> 40550	Base 3x0,75 (2,5m) Ø60x28mm <input type="checkbox"/> 40881 <input checked="" type="checkbox"/> 40882	Base 5x0,5 (2,5m) Ø60x28mm <input type="checkbox"/> 40991 <input checked="" type="checkbox"/> 40992	Ceiling suspension <input checked="" type="checkbox"/> 40780	Suspension Kit <input checked="" type="checkbox"/> 40790 (2m)



Accessories pages 159-159.

5 YEARS WARRANTY | 
 50.000 HOURS | 
 IP 40 | 
 230 VAC | 
 PF >0,9 | 
 CRI 80/93 | 
 | 
 | 
 | 
 | 
 3,37m Max | 
 |