


Urban asymmetric



Control accessories pages 282-289.

Technical Information

Power	25W / 31W / 37W / 43W / 55W
Lumens	1.650 lm - 4.290 lm
Installation	Surface / Pendant
Material	Aluminium
PCB	Flex

Code	Diffuser (Angle)	Size	CCT (lm/W) - Power/m	Driver	Colour
Code 6	Opal asym. 8	1.130mm 3	2.700K (66 lm/W) - 22W/m 2	On / Off 1	<input type="checkbox"/> White (9003) 1
		1.410mm 4	3.000K (72 lm/W) - 22W/m 3	Dali 2	<input checked="" type="checkbox"/> Custom RAL C
		1.690mm 5	4.000K (78 lm/W) - 22W/m 4	Push 3	<input checked="" type="checkbox"/> Electrolytic Plating
		1.970mm 6		Casambi 5	
		2.530mm 7			

Code: **6** **8** **1**

Consult delivery terms and conditions.
*Create your code according to your preferences.

Accessories

End caps <input type="checkbox"/> 40721 <input checked="" type="checkbox"/> 40722 <input type="checkbox"/> 40723	Joint 180° <input checked="" type="checkbox"/> 40220 <input type="checkbox"/> 40550	Joint 90° <input checked="" type="checkbox"/> 40550	Base 3x0,75 (2,5m) Ø60x28mm <input type="checkbox"/> 40881	Base 5x0,5 (2,5m) Ø60x28mm <input type="checkbox"/> 40991	Ceiling suspension <input checked="" type="checkbox"/> 40780	Suspension Kit <input checked="" type="checkbox"/> 40790 (2m)



Accessories pages 158-159.

5 YEARS WARRANTY | 50.000 HOURS | IP 40 | 230 VAC | PF >0,9 | CRI ≥95 | | | | | 3,37m Max | | | PUSH |