





# Industrial

**BENEITO FAURE**  
passion for led light

New

Ufo Lens switch  
60W / 80W / 100W


Ufo Lens switch  
90W / 120W / 150W



Technical Information

Power	Switch 60W / 80W / 100W	Switch 90W / 120W / 150W
Installation	Surface	Surface
Color Temperature	Switch 3.000K / 4.000K / 5.000K	Switch 3.000K / 4.000K / 5.000K
Lumens	131-167 lm/W	128-167 lm/W
Material	Aluminium	Aluminium
Finishes	Black	Black
Code	■ 5147	■ 5148

Accessories



Lira 100W/150W/200W  
■ 4566



5 YEARS WARRANTY | 50.000 HOURS | → | IP 65 | 100/260 VAC | PF >0,9 | CRI ≥80 | | CABLE 2M | 60° 90° 110° | 50/60 Hz | IK10 | +45°C -25°C | CCT SWITCH | POWER SWITCH | >6KV | 1

New

Ufo Lens switch  
120W / 160W / 200W


Ufo Lens switch  
140W / 190W / 240W



Technical Information

Power	Switch 120W / 160W / 200W	Switch 140W / 190W / 240W
Installation	Surface	Surface
Color Temperature	Switch 3.000K / 4.000K / 5.000K	Switch 3.000K / 4.000K / 5.000K
Lumens	123-169 lm/W	125-156 lm/W
Material	Aluminium	Aluminium
Finishes	Black	Black
Code	■ 5149	■ 5150

Accessories



5 YEARS WARRANTY | 50.000 HOURS | → | IP 65 | 100/260 VAC | PF >0,9 | CRI ≥80 | | CABLE 2M | 60° 90° 110° | 50/60 Hz | IK10 | +45°C -25°C | CCT SWITCH | POWER SWITCH | >6KV | 1



Ufo Lens switch



Ufo Lens Dali 100W

Ufo Lens Dali 150W



Technical Information

Power	100W	150W
Installation	Surface	Surface
Color Temperature	4.000K / 5.000K	4.000K / 5.000K
Lumens	16.000 lm / 16.200 lm	24.000 lm / 24.200 lm
Material	Aluminium	Aluminium
Finishes	Black	Black
Code	■ 4.000K 4915 ■ 5.000K 4916	■ 4.000K 4917 ■ 5.000K 4918

Accessories





5 YEARS WARRANTY | 50.000 HOURS | → | IP 65 | 100/260 VAC | PF >0,9 | CRI ≥80 | | CABLE 2M | 60°/90°/120° | 50/60 Hz | IK10 | +50°C / -30°C | >4KV | | 1



Ufo Lens Dali 200W



Ufo Lens Dali 240W



Technical Information

Power	200W	240W
Installation	Surface	Surface
Color Temperature	4.000K / 5.000K	4.000K
Lumens	32.000 lm / 32.200 lm	38.400 lm
Material	Aluminium	Aluminium
Finishes	Black	Black
Code	■ 4.000K 4919 ■ 5.000K 4920	■ 4.000K 4921

Accessories



5 YEARS WARRANTY | 50.000 HOURS | → | IP 65 | 100/260 VAC | PF >0,9 | CRI ≥80 | | CABLE 2M | 60°/90°/120° | 50/60 Hz | IK10 | +50°C / -30°C | >4KV | | 1



### Rotable Lens

60°



Ufo lens 100W

1m	5m	11m
9.113 lx	365 lx	75 lx

Ufo lens 150W

1m	7m	14m
13.670 lx	279 lx	70 lx

Ufo lens 200W

1m	8m	16m
18.226 lx	225 lx	71 lx

Ufo lens 240W

1m	9m	19m
26.635 lx	329 lx	74 lx





90°



1m	5m	10m
7.867 lx	315 lx	79 lx

1m	6m	13m
11.800 lx	328 lx	70 lx

1m	7m	15m
15.733 lx	321 lx	70 lx

1m	9m	19m
26.654 lx	292 lx	73 lx

120°



1m	5m	10m
6.638 lx	266 lx	66 lx

1m	6m	12m
9.956 lx	277 lx	69 lx

1m	7m	14m
13.275 lx	271 lx	68 lx

1m	9m	19m
15.882 lx	324 lx	68 lx









## Light output


1m	7m	14m
14.401 lx	294 lx	73lx

### Ufo 300W



### Technical Information

Power	300W
Installation	Surface
Color Temperature	4.000K
Lumens	39.000 lm
Material	Aluminium
Finishes	Gray
Code	■ 4.000K 3972



\*Lira included.

5 YEARS WARRANTY | 50.000 HOURS | → | IP 65 | 100/260 VAC | PF >0,9 | CRI ≥80 | | CABLE 2M | 110° | 50/60 Hz | | +50°C -30°C | >4KV | 1