


New

Tubi wall



Control accessories pages 282-289.

\*Finished luminaire. Includes base wall and end caps (aluminium).




Technical Information

Power	35W / 44W / 53W
Lumens	3.500 lm - 5.883 lm
Installation	Wall
Material	Aluminium
PCB	Rigid

Code	Diffuser (Angle)	Size	CCT (lm/W) - Power/m	Driver	Colour
Code <b>7</b>	Opal (270°) <b>9</b>	1.130mm <b>3</b>	<b>2.700K</b> (100 lm/W) - 31W/m <b>2</b>	On / Off <b>1</b>	<input type="checkbox"/> White (9003) <b>1</b>
		1.410mm <b>4</b>	<b>3.000K</b> (105 lm/W) - 31W/m <b>3</b>	Dali <b>2</b>	<input type="checkbox"/> Black (9005) <b>2</b>
		1.690mm <b>5</b>	<b>4.000K</b> (111 lm/W) - 31W/m <b>4</b>	Push <b>3</b>	<input checked="" type="checkbox"/> Custom RAL <b>C</b>
			<b>RGB-W</b> (100 lm/W) - 31W/m <b>8</b>	Casambi <b>5</b>	
			<b>2.700-5.500K</b> (105 lm/W) - 31W/m <b>9</b>	Tuya <b>7</b>	

Code: **7** **9**



Consult delivery terms and conditions.

\*Create your code according to your preferences. RGB-W and CCT 2.700-5.500K only works with driver 5 Casambi and 7 Tuya.

