



Zibor

Selen



Technical Information

|                   |
|-------------------|
| Power             |
| Installation      |
| Color Temperature |
| Lumens            |
| Material          |
| Finishes          |

|                     |
|---------------------|
| 12W                 |
| Surface             |
| 3.000K / 4.000K     |
| 1.200 lm / 1.250 lm |
| Polycarbonate       |
| White / Black       |

|                     |
|---------------------|
| 12W                 |
| Surface             |
| 3.000K / 4.000K     |
| 1.200 lm / 1.250 lm |
| Polycarbonate       |
| White / Black       |

|      |
|------|
| Code |
|------|

|   |            |      |
|---|------------|------|
| ○ | 3.000K     | 4670 |
| ○ | 4.000K     | 4669 |
| ● | 3.000K     | 4830 |
| ● | 4.000K     | 4829 |
| ① | Custom RAL |      |

|   |            |      |
|---|------------|------|
| ○ | 3.000K     | 4668 |
| ○ | 4.000K     | 4667 |
| ● | 3.000K     | 4828 |
| ● | 4.000K     | 4827 |
| ① | Custom RAL |      |

Accessories




Linear Joint IP68  
Ø26x95mm  
■ 5671 New



T Joint IP68  
74x118mm  
■ 5672 New



X Joint IP68  
122x122mm  
■ 5673 New



① Consult delivery terms and conditions.

3 YEARS WARRANTY

25.000 HOURS

IP 65

220/240 VAC

PF >0,9

CRI ≥80

120°

50/60 Hz

IK02

+40°C  
-20°C

1/10