





NEW

Zero T



Equipment



\*Finished luminaire. Includes power supply, suspension kit and power cable.

Control accessories: page 327

pages 326-333

pages 334-335



Technical Information

Power	148W / 218W
Lumens	8.880 lm - 15.696 lm
Installation	Pendant
Material	Aluminium 6063
PCB	Flex (Fine 56)

Code	Diffuser (Angle)	Size	CCT (lm/W)	Driver	Colour
Code <b>Z</b>	Opal (100°) <b>T</b>	400+700+1.000mm <b>4</b>	2.700K (60 lm/W) <b>2</b>	On / Off <b>1</b>	○ White (9003) <b>1</b>
		700+1.000+1.400mm <b>5</b>	3.000K (66 lm/W) <b>3</b>	Casambi <b>5</b>	● Black (9005) <b>2</b>
			4.000K (72 lm/W) <b>4</b>	Tuya <b>7</b> ⓘ	● Matt Gold <b>4</b>
			2.700-5.500K (70 lm/W) <b>9</b>	Dali / Push <b>8</b> ⓘ	● Silver <b>5</b>
					ⓘ  Custom RAL

Code: **Z** **T** ■ ■ ■ ■ ■



ⓘ Consult delivery terms and conditions.

\*Create your code according to your preferences. RGB-W and CCT 2.700-5.500K only works with driver 5 Casambi and 7 Tuya.

